

FieldLink[®]

DeviceNet



Design

a) Pair 02YS(ST) 1X2X0.67/1.9-120 LI VZN

Wire

Stranded tinned copper wire 19 X 0.13

Insulation of foamed Polyethylene (PE) with skin

Wall thickness about 0.6 mm

∅ 0.67 mm (0,026 in)

∅ 1.9 mm (0.075 in)

2 wires, WH and BU side by side

Alulamine foil overlapped, applied longitudinally

b) Pair LIY(ST) 1X2X0.38/1.4 VZN

Wire

Stranded tinned copper wire 19 X 0.16

Insulation of Polyvinylchloride (PVC)

Wall thickness about 0.3 mm

∅ 0.75 mm (0.030 in)

∅ 1.4 mm (0,055 in)

2 wires, RD and BK side by side

Alulamine foil overlapped, applied longitudinally

Core:

Central element: Stranded tinned copper drain wire 0.38 mm² (19x0.16)

1 Pair 02YS(ST) 1X2X0.67/1.9-120 LI VZN

1 Pair LIY(ST) 1X2X0.38/1.4 VZN

Shield braiding of tinned copper wires 0.13 mm dia

Coverage about 70%

∅ 4.6 mm (0.181 in)

Jacket:

Polyvinylchloride (PVC) GY
 Wall thickness about 0.9 mm

∅ (6.4 ±0.3) mm (0.252 ±0.012 in)

Printing: LEONI L DeviceNet Thin Cable 2x23AWG 2x22AWG SHIELDED (UL) E119100 CMG 75°C or
 CL2 FT4 Sun Res

Electrical data at 20°C

Conductor resistance	(Pair to a)	≤	90	Ohm/km
Conductor resistance	(Pair to b)	≤	55	Ohm/km
Capacitance (1 kHz wire/wire)	(Pair to a)	≈	39.8	nF/km
Characteristic impedance (1 MHz)	(Pair to a)		(120 ±12)	Ohm
Signal run time	(Pair to a)	≤	4.46	ns/m
Capacity unbalanced to ground	(Pair to a)	≤	3937	pF/km
Operating voltage (peak)		≤	300	V
Insulation resistance		≥	20	MOhm*km
Test voltage (wire/wire/screen rms 50Hz 1min)		=	2000	V

Frequency (kHz)	125	500	1000
Attenuation typ. (dB/100m) (Pair to a) (dB/100ft)	0,95 (0,3)	1,64 (0,5)	2,29 (0,7)

Mechanical and thermal characteristics

Conductor/Screen material acc. to DIN EN 13602 Cu-ETP-A...-B
 Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table 2/A (HD 624.3)
 Insulating material acc. to DIN EN 50290-2-21 (VDE 0819), compoundtype TI53 (HD 624.1)
 Jacket material acc. to DIN VDE 0207, compoundtype YM3
 Sunlight resistant acc. to UL 1581 Sec.1200
 Flame retardant acc. to UL 1685 (CSA FT 4)

UL File E119100 Vol.1 Sec.17 Page 4

UL File E116441 Vol.1 Sec.7 Page 4

Application / Special feature:

Permissible temperature range : -20°C (-4°F) up to +80°C (+176°F)
 Min. bending radius allowed : repeated 10X ∅, single 3,75X ∅
 PVC weight with Phthalate : 21.1 Kg/km
 PVC weight without Phthalate : 2.7 Kg/km
 Weight about : 60 Kg/km (40,2 lb/1000ft)

Designation of order of order:

L45467-F16-W55
 207037
 02YS 1X2X0.67/1.9-120 LI VZN PIMF
 LIY CY 1X2X0.38 VZN PIMF GY
 1000 m (3281 ft) on non-returnable reel