


FieldLink® PROFIBUS



Design

Wire

Bare copper wire ∅ 1.05 mm (0,041 in)
 Insulation of foamed Polyethylene (PE) with skin ∅ 2.55 mm (0,100 in)

Core

2 wires, RD and GN twisted to a pair
 Plastic tape, overlapped
 Inner-Jacket Polyvinylchloride (PVC) ∅ 5.4 mm (0,213 in)
 Alulaminat foil overlapped, applied longitudinally
 Shield braiding of tinned copper wires 0.15 mm dia
 Coverage about 90% ∅ 6.2 mm (0.244 in)

Jacket

Polyvinylchloride (PVC) BK
 Wall thickness about 0.9 mm ∅ (8.0 ±0.4) mm (0.315 ±0.016 in)

Printing: "sequential length in metres" BizLink Special Cables Germany PROFIBUS FMS ES L45467-J20-C225
 * 18AWG (SHIELDED) (UL) E119100 CM 75°C or CL3 or AWM 21694 600V SUN RES OIL RES I *
 "internal lot number"
 Textintervals about 1000 mm

Electrical data at 20°C

Conductor resistance	≤	22	Ohm/km
Insulation resistance	≥	10	MOhm*km
Capacitance (1 kHz wire/wire)	≈	50	nF/km
Capacitance (1 kHz wire/screen)	≈	92	nF/km
Operating voltage		100	V
UL-Rating		600	V
Test voltage (wire/wire/screen rms 50Hz 1min)		2000	V
Characteristic Impedance (31.25 KHz)		(100 ±20)	Ohm
Attenuation (39 KHz)	≤	3	dB/km
Capacitance unbalance e	≤	2	nF/km
Inductance (31.25 KHz)		650	µH/km
Surface transfer impedance (20 MHz)	≤	5	mOhm/m
rel. velocity of propagation	≈	81	%

Mechanical and thermal characteristics

Conductor material acc. to DIN EN 13602 Cu-ETP-A...

Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-23 (VDE 0819), table 2/A (HD 624.3)

Jacket material acc. to DIN VDE 0207, compoundtype YM5

Oil resistant acc. to UL 758 Sec. 15 (60°C)

Flame retardant acc. to UL 1685 (Vertical tray) CM

Sunlight resistant acc. to UL 1581 Sec.1200

File E119100 Vol.1 Sec.16 Page 6 (CM)

File E116441 Vol.1 Sec.6 Page 6 (CL3)

UL-Style 21694

Application / Special feature

Flame retardant acc. to IEC 60332-1-2

Permissible temperature range : -20 °C (-4 °F) up to 80 °C (176 °F)

Min. bending radius allowed : repeated 10X \varnothing , single 5X \varnothing

Tensile strength \leq 150 N

PVC weight with Phthalate : 47.5 Kg/km

PVC weight without Phthalate : 0.0 Kg/km

Weight about : 103 Kg/km (69 lb/1000ft)

Designation of order

L45467-J20-C225

228880

02YSY(ST)CY 1X2X1.0/2.55-100 OE FR

1000 m (3281 ft) on non-returnable reel

Product has not been tested and classified according to the CPR (EU/305/2011).

The product shall not be permanently installed in buildings in the EU.