


FieldLink®

LI9YC(ST)11Y 4X2X0.15 GN



Design

Wire

Stranded bare copper wire 19 X 0.1 (26AWG)

ø 0.5 mm

Insulation of polypropylene

ø 1.0 mm

2 wires twisted to a pair

Core

4 pairs stranded + fillers

Sequence of colors: WHBU/BU - WHOG/OG - WHGN/GN - WHBN/BN

Plastic tape, overlapped

Shield braiding of tinned copper wires 0.1 mm dia

Coverage about 90%

Plastic tape conductiv

Jacket

Polyurethane (PUR) GN

Wall thickness about 0.8 mm

ø (6.8 -0.3) mm

Printing: "sequential length in metres" BizLink Special Cables Germany TRAILING CABLE 4X2X0.15 *
E130266 AWM 20963 80°C 30V * "internal lot number"

Electrical data at 20°C

Loop resistance	≤	260 Ohm/km
Resistance difference	≤	3 %
Signal running time	≤	5.55 ns/m
Insulation resistance	≥	150 MOhm*km
Characteristic impedance at 100 MHz		(100 ±5) Ohm
Ground unbalance attenuation at 64 kHz	>	43 dB
Capacity unbalanced to ground at 1 kHz	≤	3400 pF/km
Return loss 4 – 20 MHz	≥	23 dB
20 – 100 MHz	≥	23 dB - 10 log (f/20)
Surface transfer impedance 10 MHz	≤	70 mOhm/m
Operating voltage	≤	60 V
Test voltage (wire/wire/screen rms 50Hz 1min)		700 V
Capacitance 800 Hz		50 nF/km

CONFIDENTIAL: This document and its content must be treated strictly confidentially and are property of BizLink Special Cables Germany GmbH

Frequency (MHz)	1	4	10	16	20	31.25	62.5	100
Attenuation typ. (dB/100m)	3	6	9	11	12	16	24	31
Near crosstalk (dB) ≥	62	53	47	44	42	40	35	32

Mechanical and thermal characteristics

Conductor material acc. to DIN EN 13602 Cu-ETP-A...

Screen material acc. to DIN EN 13602 Cu-ETP-A...-B

Insulating material acc. to DIN EN 50290-2-25, compound type full PP (HD 624.5)

Jacket material acc. F45052-F5100 (similar to DIN VDE 0282)

Flame test acc. to IEC 60332-1-2

UL-Style 20963 (80°C/30V)

Other characteristics

RoHS compliant

Torsion ≤ ±30°/m (must be tested)

Silicon free

FCKW free

Halogen free

Oil resistance

Trailing cable for following requirements:

- 10 million bending cycles (must be testified)
- bending radius 7.5x max. ø
- at a speed of 180m/min
- acceleration 5 m/s²

Pulling force with ≤ 100N

Permissible temperature range : -40 °C up to + 80°C

Weight about : 55 Kg/km

Application / Special feature

Similar to Cat.5

Designation of order

L45581-B42-K8

202304

BCA0182

LI9YC(ST)11Y 4X2X0.15 GN

2000 m on non-returnable reel

Product has not been tested and classified according to the CPR (EU/305/2011).

The product shall not be permanently installed in buildings in the EU.